

Product No: MK-MoS2-SP
Molybdenum Disulfide (MoS2) Dry Lubricant Spray
for Dry lubricity applications (also known as Moly Spray),

- **Ideal where wet film lubricants cannot be used**
- **Bonds well with substrate and forms coating film**
- **Wide temperature range of -50°C to + 450°C**
- **High Load bearing properties**
- **Contains no fluorocarbons or lead**
- **Not harmful to Ozone**

Suggested applications:

- **Automotive Parts, Car Engine, Piston & Piston Cylinders**
- **Bearings**
- **Lubricant coating on chain drives**
- **Cams and Cam followers**
- **Power Transmission Components**
- **Machinery Components, Precision Gears**
- **Plastic Molds & Extrusion Dies for release**
- **Aerospace & Defense Components**
- **Marine Parts**
- **Sliding or Rotating Components**
- **Valve Components & Actuators**
- **Rollers, Spindles, Shafts & Seals**
- **Robotics**
- **Sporting Goods**
- **Cutting Tools, Blades, Slitters & Knives, Punches & Dies**
- **Bullet & Ammunition Parts**

Packing: 13 Oz/369 grams per can (Read MSDS before use)

Product Numbers:

MK-MoS2-SP/01: 1 can

MK-MoS2-SP/02: Box of 12 cans

MK-MoS2-SP/03: Carton of 48 cans



www.lowerfriction.com

M K Impex Corp.

6382 Lisgar Drive

Mississauga, Ontario L5N 6X1

Canada

Phone: 416-509-4462; Fax: 905-824-1259

E-mail: sales@lowerfriction.com